



**Inside Mount Vertical & Horizontal Tracks**

Inside Mount Opening sizes cannot exceed 1/2" (plus or minus)

	Fastener	5/16" Tapcon		#14 ELCO Self Drill
	Edge Distances	1 1/2"		1/2" 3/8"
	Outside of Track	DLO		
		Substrait	Wood	1/4" Alum 3/16" Steel
		Screen		
		Track		
	Fastener	1/4" Tapcon	1/4-20 Tampin	#14 ELCO Self Drill
	Edge Distances	2.1875"	3" 1/2"	3/8"
	Outside of Track	DLO		
	Substrait	Concrete	1/4" Alum 3/16" Steel	
	Screen			
	Track			
Fastener	5/16" Tapcon	1/4-20 Tampin	#14 ELCO Self Drill	
Edge Distances	4"	3" 1/2"	3/8"	
Outside of Track	DLO			
	Substrait	Grout/Block	1/4" Alum 3/16" Steel	
	Screen			
	Track			

**FIXED TRACKS ARE LIMITED TO 250" (OUTSIDE DIMENSION) ON ANY SIDE**

**Inside /Outside Mount Vertical & Horizontal Tracks**

	<b>1 Inside Track/1 Face Mount Track</b>			
	Fastener	5/16" Tapcon		#14 ELCO Self Drill
	Edge Distances	1 1/2"		1/2" 3/8"
	Outside of Track	DLO + 2"		1" 7/8"
		Substrait	Wood	1/4" Alum 3/16" Steel
		Screen		
		Track		
	Fastener	1/4" Tapcon	1/4-20 Tampin	#14 ELCO Self Drill
	Edge Distances	2.1875"	3" 1/2"	3/8"
Outside of Track	DLO + 2 3/16"	Add 7" to DLO	1" 7/8"	
	Substrait	Concrete	1/4" Alum 3/16" Steel	
	Screen			
	Track			
Fastener	5/16" Tapcon	1/4-20 Tampin	#14 ELCO Self Drill	
Edge Distances	4"	3" 1/2"	3/8"	
Outside of Track	DLO + 4 1/2"	Add 7" to DLO	1" 7/8"	
	Substrait	Grout/Block	1/4" Alum 3/16" Steel	
	Screen			
	Track			